

---

# REPLACEMENT INSTRUCTIONS

## KICK-DOWN JACK WARNING SWITCH

---

**THIS WARNING SWITCH KIT WILL BE USED TO REPLACE ANY EARLY MODEL 2-WIRE WARNING SWITCH ON KICK-DOWN STYLE JACKS. THIS SWITCH KIT CANNOT BE USED TO REPLACE A 3-WIRE WARNING SWITCH.**

**THERE ARE THREE POSSIBLE SITUATIONS THAT CAN OCCUR WHEN REPLACING A SWITCH.**

1. REPLACEMENT OF A 2-WIRE WARNING SWITCH THAT HAS A 2-PIN PACKARD TOWER. DISREGARD THE ADAPTER IT IS NOT NECESSARY.

2. REPLACEMENT OF A 2 WIRE WARNING SWITCH THAT HAS A 1-PIN PACKARD TOWER AND RING TERMINAL. USE THE ADAPTER AS SHOWN BELOW.

3. REPLACEMENT OF A 2-WIRE WARNING SWITCH WITHOUT ANY TYPE OF PACKARD CONNECTOR. USE THE ADAPTER BY ELIMINATING THE 1-PIN PACKARD TOWER AND SPLICING THE ADAPTOR WIRES TO THE EXISTING HARNESS WITH SOLDER. SHRINK TUBE THE SPLICE.

THE RING TERMINAL OF THE ADAPTER CAN BE GROUND-ED AT THE SAME LOCATION AS THE ORIGINAL WARNING SWITCH.

